# TECHNICAL DATA SHEET

#### Dawlish

Exposed Thermostatic Dual Control Shower Valve with Premium Flexible Riser Kit

SDCDUAL09 (Chrome)

#### **Product** Specification

Product	Codes	&	Finishes:

**Maximum Temperature: Inlet Connections: Working Pressures: Dimensions for Fitting:** 

SDCDUALI0 (Vintage Gold) Pre-set to 42oC 15mm Compression Min 0.1 Bar, Max 5.0 Bar 635 (H) mm, 136-158 (W) mm, 157 (D) mm

### **Additional** Information

- 5 Year Guarantee
- Adjustable inlet centres on the valve mean you can use existing pipework with centres measuring anything between 136mm and 158mm.
- · Factory fitted regulators means this is a water saving shower
- Supplied with single mode handset, hose and adjustable riser
- · Matching taps available

## **Flow** Rates (litres per minute)

System Pressure	0.1bar	0.2bar	0.5bar	Ibar	2bar	3bar	5.0bar
With Flow Regulators (mixed)	4.78	6.75	13	15.1	14.7	14.7	14.7
Without Flow Regulators (mixed)	8.6	12.16	19.23	27.2	38.47	47.11	60.82

#### **Technical Advice:**

For further information please call 0844 701 8503 or email technical@heritagebathrooms.com.

#### **Guarantee:**

5 Year Guarantee covering manufacturing faults.

Heritage Bathrooms, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG Telephone: 0844 701 8501 Facsimile: 0844 701 8502 Web Site: www.heritagebathrooms.com Email: technical@heritagebathrooms.com

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Heritage Bathrooms pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.



157 136-158 (centres)





