TECHNICAL DATA SHEET



BATHROOMS

Glastonbury

Recessed Thermostatic Dual Control Shower Valve with Premium Fixed Head and Flexible Riser Kits

Product Specification

Product Codes & Finishes: SGDUAL03 (Chrome)

SGDUAL04 (Vintage Gold)

Connection Inlet: 15mm Compression

Maximum Temperature: Pre-set 42oC

Pressure Range: Min 0.2 Bar, Max 5.0 Bar

Cavity Depth: 58-75mm

Inlet Centres: 635 (H) mm, 185 (W) mm, 335 (D) mm

Additional Information

- 5 Year Guarantee
- Chrome plated to BS EN 248:2002
- Supplied with shower arm, 155mm shower rose, adjustable riser, shower hose, slider, hose retainer, and handset
- Requires rear access to service the filters
- Cartridge can be accessed from the front
- Matching taps available

335 155 635 250 63 - 92 185

Flow Rates (litres per minute)

System Pressure	0.2bar	0.5bar	lbar	2bar	3bar	5bar
Outlet I	8.5	13.44	19	26.87	32.91	42.49
Outlet 2	8.27	13.08	18.5	26.16	32.04	41.37

Technical Advice: For further information please call 0844 701 8503

or email technical@heritagebathrooms.com.

Guarantee: 5 Year Guarantee covering manufacturing faults.





