# TECHNICAL DATA SHEET

## Glastonbury

Exposed Sequential Valve with Bottom Outlet

### **Product** Specification


Product Codes & Finishes:
Connection Inlet:
Maximum Temperature:
Pressure Range:
Inlet Centres:

SGCB03 (Chrome) SGAB03 (Vintage Gold) I 5mm Compression Pre-set 42oC Min 0.1 Bar, Max 5.0 Bar

Adjustable from 136mm – 158mm

### Additional Information

- 5 Year Guarantee
- Chrome plated to BS EN 248:2002
- Supplied with 2x 8 litres per minute flow regulators
- Adjustable inlet centres mean you can use existing pipework with centres measuring anything between 136mm and 158mm.
- Factory fitted regulators means this is a water saving shower
- Matching taps available



**HERITAGE**<sup>®</sup>

BATHROOMS

#### Flow Rates (litres per minute)

System Pressure	0.1bar	0.2bar	0.5bar	Ibar	2bar	3bar	5bar
With Flow Regulators	2.41	3.41	5.39	7.62	10.78	13.2	17.04
Without Flow Regulators	8.76	10.3	18.6	27.3	39.1	48	61.7

#### **Technical Advice:**

For further information please call 0844 701 8503 or email <u>technical@heritagebathrooms.com</u>.

#### Guarantee:

5 Year Guarantee covering manufacturing faults.





Heritage Bathrooms, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG Telephone: 0844 701 8501 Facsimile: 0844 701 8502 Web Site: <u>www.heritagebathrooms.com</u> Email: <u>technical@heritagebathrooms.com</u>

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Heritage Bathrooms pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.