TECHNICAL DATA SHEET

Hartlebury

Recessed Thermostatic Dual Control Shower Valve with Fixed Head Kit

Product Specification

Product Codes & Finishes:	SHDDUAL03 (Chrome)			
	SHDDUAL04 (Vintage Gold)		1 Constr	
Maximum Temperature:	Pre-set to 42oC	. 11		
Inlet Connections:	15mm Compression	and the		Chrome Pictured
Working Pressures:	Min 0.2 Bar, Max 5.0 Bar		The se	
Cavity Depth:	45-75mm	all		
Dimensions for Fitting:	250 (H) mm, 185 (W) mm, 335 (D) mm		Contraction of the second seco	

Additional Information


- 5 Year Guarantee
- Requires rear access to service the filters
- · Cartridge can be accessed from the front
- •Supplied with shower arm and 155mm shower rose
- Matching taps available



155

335

II-0



Flow Rates (litres per minute)

System Pressure	0.2bar	0.5bar	Ibar	2bar	3bar	5bar
Open Outlet	9.39	14.85	21	29.7	36.37	46.96



delivery to showroom

Technical Advice:

For further information please call 0844 701 8503 or email technical@heritagebathrooms.com.

Guarantee:

5 Year Guarantee covering manufacturing faults.

Heritage Bathrooms, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG Telephone: 0844 701 8501 Facsimile: 0844 701 8502 Web Site: www.heritagebathrooms.com Email: technical@heritagebathrooms.com

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Heritage Bathrooms pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.



HERITAGE[®] BATHROOMS