TECHNICAL DATA SHEET

Hartlebury

Recessed Shower Valve with Integral Two Outlet Diverter

Product Specification

Product Codes & Finishes:

Maximum Temperature: Inlet Connections: Working Pressures: Cavity Depth: Inlet Centres: SHDC03 (Chrome) SHDA03 (Vintage Gold) Pre-set to 42oC I 5mm Compression Min 0.2 Bar, Max 5.0 Bar 45-75mm I 50mm

Additional Information

- 5 Year Guarantee
- Requires rear access to service the filters
- Cartridge can be accessed from the front
- Matching taps available



Flow Rates (litres per minute)

System Pressure	0.2bar	0.5bar	Ibar	2bar	3bar	5bar
Outlet I	8.5	13.44	19	26.87	32.91	42.49
Outlet 2	8.27	13.08	18.5	26.16	32.04	41.37



delivery to showroom

Technical Advice:

For further information please call 0844 701 8503 or email technical@heritagebathrooms.com.

Guarantee:

5 Year Guarantee covering manufacturing faults.

Heritage Bathrooms, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG Telephone: 0844 701 8501 Facsimile: 0844 701 8502 Web Site: www.heritagebathrooms.com Email: technical@heritagebathrooms.com

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Heritage Bathrooms pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.



HERITAGE[®]

DI