DARTMOUTH Tap Range Dartmouth BSM Brushed Brass



|--|

Features:

- Compatible with low pressure water systems, optimised for UK market
- Quarter turn ceramic discs for smooth operation and added durability
- Available in a selection of finishes

Specification					
Product Type:	Bathroom Tap				
Main Construction Material:	Brass				
Mount Type:	Deck				
Handle Type:	Lever				
Connection Inlet:	3/4" BSP				
Connection Outlet:	MI6.5xI Aerator				
Number of Tap Holes:	2				
Valve/Cartridge Type:	3/4" Ceramic Disc Valve - 1/2 Turn				
Plumbing System Requirements:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.5 bar				
Maximum Dynamic Pressure (bar):	5 bar				
Maximum Hot Water Temperature °C:	65°C				
Maximum Static Pressure (bar):	IO bar				
Flow Type:	Single				
Isolation Included:	No				

Product Certifications:



Additional Information:

Dimensions (measurements in mm) 235 165 220 150 230

Flow Rates (I/min)							
System Pressure (bar)	0.5	1	2	3	5		
Through Bath Filler (mixed)	4.3	6.4	9.0	10.6	13.7		
Through Handset (mixed)	4.0	8.0	8.0	10.3	13.3		

TECHNICAL DATA SHEET





