SALCOMBE Tap Range Salcombe Bath Filler Brushed Brass




-				
г		4	ıre	
	-10	тп		М
	u	190		r n


- Compatible with low pressure water systems, optimised for UK market
- Quarter turn ceramic discs for smooth operation and added durability
- Available in a selection of finishes

Specification						
Product Type:	Bathroom Tap					
Main Construction Material:	Brass					
Mount Type:	Deck					
Handle Type:	Cross Head					
Connection Inlet:	3/4 BSP					
Connection Outlet:	Flow Straightener					
Number of Tap Holes:	2					
Valve/Cartridge Type:	3/4 inch Ceramic Disc Valve					
Plumbing System Requirements:	Suitable for all plumbing systems					
Minimum Dynamic Pressure (bar):	0.2 bar					
Maximum Dynamic Pressure (bar):	5 bar					
Maximum Hot Water Temperature °C:	65°C					
Maximum Static Pressure (bar):	10 bar					
Flow Type:	Single Flow					
Isolation Included:	No					

Dimensions (measurements in mm)

Product Certifications:





Additional Information:

Flow Rates (I/min)									
System Pressure (bar)	0.2	0.5	ı	2	3	5			
TSACBB07 (mixed)	14.2	23.9	34.6	49.2	62.2	80.3			

TECHNICAL DATA SHEET



