



- All the dimensions are shown in millimetres
- Tube dia 20mm x 20mm
- Header tube dia 30mm x 30mm
- Bracket length - 55-75mm
- ½ inch BSP bottom opposite end connections
- Test pressure: 10 Bar
- Max working temperature: 8 Bar
- Heat output - in accordance with EN 442

Please Note:

- Please allow minimum of 100mm for valves
- Summer Element use will affect pipe centres
- The flow and return can be reversed

Premier Flat	Water Content (L)	Weight (KG)	Pipe Centres +/- 2mm	Fixing Centres (H) +/- 2mm	Fixing Centres (W) +/- 2mm	Height (mm)	Width (mm)
RXPS-0600300	2	3.4	250	429	150	600	300
RXPS-0800400	3.1	5.2	350	624	250	800	400
RXPS-0800500	3.6	6	450	624	350	800	500
RXPS-0800600	4.1	6.8	550	624	450	800	600
RXPS-1200300	3.8	6.4	250	1014	150	1200	300
RXPS-1200400	4.6	7.7	350	1014	250	1200	400
RXSP-1200500	5.4	8.9	450	1014	350	1200	500
RXPS-1200600	6.1	10.2	550	1014	450	1200	600
RXPS-1500300	5.4	9.5	250	1326	150	1500	300
RXPS-1500400	5.8	9.3	350	1326	250	1500	400
RXPS-1500500	6.7	12.2	450	1326	350	1500	500
RXPS-1500600	7.7	13.8	550	1326	450	1500	600
RXPS-1800400	7	11.6	350	1599	250	1800	400
RXPS-1800500	8.2	13.5	450	1599	350	1800	500
RXPS-1800600	9.3	15.4	550	1599	450	1800	600
RXPS-0600600	3.2	5.4	550	429	450	600	600
RXPS-0600800	4.0	6.7	750	429	650	600	800
RXPS-06001000	4.8	8.1	950	429	850	600	1000

Installation:

