Freestanding Bath Shower Mixer Installation Instruction

- All parts should be removed from their packaging and inspected for any transport damage and completeness prior to installation.
- You should read these instructions throughout before commencing installation. We do not accept responsibility for problems that may occur through improper installation.
- Always ensure you have sufficient hot and cold water pressure available to allow correct function before specifying or installing this product.
- Before installing the bath filler it is essential that you thoroughly flush through the supply
 pipes in order to remove any remaining solder, swarf or impurities from your system. Failure
 to carry out this simple procedure could cause problems or damage to the workings of the
 product.
- We strongly recommend installing particle filters and isolation valves to both the hot and cold feed pipes in an accessible position. This will help to prevent premature failure of the valves and ease any future maintenance.
- All serviceable parts should be given suitable access to allow easy future maintenance.
- Shut off your water heating system and ensure that your mains stopcock is closed. Ensure both the hot and cold water supplies are isolated before commencing installation.
- You should ensure that the product will both fit into the depth of the mounting surface available and reach the required outlet position before installation.
- Loosely position the tap and connecting pipes to check if any alteration to the existing pipework is required, if this is the case do this now.
- Before starting installation make sure that the water feed is closed.






Floorstanding Bath/Shower Mixer with Easy-Box Installation Instruction

1. Remove all parts from the packaging and inspect for any transport damage and completeness prior to installation



2. Fit the extensions as below and then connect the spout and tube using M3 Allen Key



3. Feed the chrome cover plate over the standpipe





4. Wrap PTFE tape on the supplied elbows and install elbows into the easy-plumb box





5. Set the easy-plumb box into the recess in the floor and ensure it is level using the spirit level provided



6. Connect to elbows with 1/2" female iron connections (not provided)



7. Fix box to the floor with toggle bolts provided



8. Finish the floor ensuring nothing gets inside the easy-plumb box - the box should be slightly proud of the finished tiled floor level



9. Remove cover plate, spirit level, blanking caps. (Remover tool: M4 Allen Key)



10. Join the cover plate and copper ring (Using M3 Allen Key)








11. Fit the cover plate with copper ring over the stand pipe



12. Fit the copper pipe from the standpipe to the easy-box connector, ensuring hot and cold align correctly relating to lever control



13. Connect metal plate to easy-box (Using M4 Allen Head Screws)



14. Slide the chrome cover plate down and install the handset.





After Installation

- Once you have visually checked the installation of the new tap and all connections, ensure that all other fittings are closed except the tap which should be left open.
- Turn on your water heating system and ensure that your mains stopcock is open. Reconnect both the hot and cold water supplies to this fitting.
- Check the function of flow and the function of hot, cold and mixed water.
- Turn off the tap and check carefully for any leaks around all connections on the fitting and
 adjoining plumbing. If possible return to the installation after a longer period to double check
 for slower leaks. If pressure testing equipment is available check the installation to the
 maximum recommended pressure.
- Clean the tap to remove any marks created during installation as instructed then place a bag over the product to protect the tap until it is ready for use.

Care Instructions for your Freestanding Bath Shower Mixer

To maintain the appearance of this tap, ensure that it is regularly cleaned only using a clean, soft damp cloth. A solution of warm water and a mild liquid detergent may be used where necessary, and then the fitting rinsed thoroughly and wiped dry. Any other cleaning action or cleaning products will invalidate your warranty. If the product has a removable spout diffuser it can be unscrewed and cleaned periodically in warm water to maintain flow.

Abrasive cleaners, scouring cleaners, limescale cleaners and acidic cleaners must not be used under any circumstances.

Avoid contact with all solvents (including chlorinated solvents, ketones or acetones) as these may result in surface deterioration or etching.

Also avoid contact with any harsh household chemicals such as bleach cleaners, drain cleaners, rust removers, paint strippers, toilet bowl cleaners, toothpaste, mouthwash, bar keepers friend or Brasso.