



**Product**

Arcane Curve 50, Arcane Curve 60 & Arcane Curve 120 - Black / Brushed Brass

**Article Number**

Arcane Curve 50 Black: 79500100  
Arcane Curve 50 Brushed Brass: 79500200  
Arcane Curve 60 Black: 79500300  
Arcane Curve 60 Brushed Brass: 79500400  
Arcane Curve 120 Black: 79500500  
Arcane Curve 120 Brushed Brass: 79500600

**Product Description**

Black/Brushed Brass framed mirror with ambient LED illumination

### Technical Data

Net weight (kg)	Arcane Curve 50: 4.9kg / Arcane Curve 60: 6.9kg / Arcane Curve 120: 11.9kg
Light Source	LED
Light Source Average Lifespan	30,000hrs - 50,000hrs
Total Rated Wattage (W)	Arcane Curve 50: TBC / Arcane Curve 60: TBC / Arcane Curve 120: TBC
Lumens (Lm)	Arcane Curve 50: 1230lm / Arcane Curve 60: 1470lm / Arcane Curve 120: 2070lm
Kelvins (k)	Arcane Curve 50/60/120: 2700-6500K
Is the mirror dimmable?	No
Energy Rating	F
Does the mirror require an earth connection?	No
Can I bypass the sensor so the mirror comes on with the main room light?	No
Colour temperature change (CTC) technology?	Yes
What IP rating is the mirror?	IP44 rated
What orientation can the mirror be hung in?	Portrait / Landscape
Is the heated pad only on when the mirror is illuminated?	Yes
How long is the warranty?	5 years from date of purchase on silvering coating on mirror 2 years from date of purchase on electrical components in the mirror

#### Electrical Safety Information

HiB recommends that all electrical bathroom products should only be fitted by a suitably qualified, Part P registered electrician in accordance with current IEE regulations.

Ensure mains power supply is switched off before starting installation.

Before drilling, ensure there are no hidden cables or pipes in the wall.

**HiB recommend you receive the product before commencing with installation as all sizes and measurements are approximate.**

**HiB try and ensure all measurements are as accurate as possible.**

**In the interest of continuous product development, HiB reserves the right to alter specification as necessary. E & OE.**