## APL BF C

# APPEAL Tap Range Appeal Bath Filler Chrome



Specification				
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Paddle Lever			
Connection Inlet:	3/4" BSP			
Connection Outlet:	Housed M24 Aerator			
Number of Tap Holes:	2			
Valve/Cartridge Type:	3/4" Short Stem Ceramic Disc Valve			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.2 bar			
Maximum Dynamic Pressure (bar):	5 bar			
Maximum Hot Water Temperature °C:	60°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single			
Isolation Included:	No			

#### Features:

- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- Robust metal fixing nut to secure the tap in place reducing the risk of loosening over time.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years. Salt spray tested to ensure added durability.
- 10-year parts and 1 year labour guarantee for peace of mind.
- Also available in black and brushed brass.
- Co-ordinating Bathroom taps available

#### **Product Certifications:**



WRAS Certificate No: 2309905 WRAS Expiry Date: 30/09/2028

For more products, visit our website: <a href="http://www.bristan.com">http://www.bristan.com</a>



Dilliensi	ons (medsareme		
140	<b>~</b> I		
105	<u> </u>	230	<b></b>
50	65	180	

Dimensions (measurements in mm)

Flow Rates (I/min)									
System Pressure (bar)	0.2	0.5	1	2	3	5			
APL BF C (mixed)	24.2	40.4	57.2	80.9	99	127.9			

### TECHNICAL DATA SHEET



