## SAF ES SMBAS BB

# SAFFRON Tap Range Saffron Eco start Small Basin Mixer Brushed Brass



Specification					
Product Type:	Bathroom Taps				
Main Construction Material:	Brass				
Mount Type:	Deck				
Handle Type:	Lever				
Connection Inlet:	1/2" BSP Flexible Tails				
Connection Outlet:	M24 5lpm Coin-Slot Aerator				
Number of Tap Holes:	1				
Valve/Cartridge Type:	28mm Eco-Start Cartridge				
Plumbing System Requirements:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.5 bar				
Maximum Dynamic Pressure (bar):	5 bar				
Maximum Hot Water Temperature °C:	60°C				
Maximum Static Pressure (bar):	10 bar				
Flow Type:	Single				
Isolation Included:	No				

Dimensions (measurements in mm)

#### Features:

- Eco Start technology saves energy by having cold water as the default central start position of the tap handle. Hot water is only activated when the tap lever is moved from the central position, so your boiler is not unnecessarily fired up.
- This tap has a flow regulator, which limits the flow of water to 5 litres per minute, reducing the amount of water you use.
- Long life ceramic cartridge for added durability and smooth control.
- Everything you need in the box including flexible tails and clicker waste so nothing to buy separately.
- On-trend brushed brass finish to make a statement in your bathroom.

#### **Product Certifications:**



WRAS Certificate No: 2307906 WRAS Expiry Date: 31/07/2028

Water Label 44.8 I/min

	135	
	100	1
Ī		
135		90
		90
Ţ	45	<u>!</u>

Flow Rates (I/min)									
System Pressure (bar)	0.5	0.5	1	2	3	5			
SAF ES SMBAS BB (mixed)	2.5	2.5	3.5	4.5	4.8	5.1			

### TECHNICAL DATA SHEET



