SAF BF C

SAFFRON Tap Range Saffron Bath Filler Chrome



Specification				
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Loop			
Connection Inlet:	3/4" BSP			
Connection Outlet:	M24 Recessed Honeycomb Aerator			
Number of Tap Holes:	2			
Valve/Cartridge Type:	3/4" Short Stem Ceramic Disc Valve			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.2 bar			
Maximum Dynamic Pressure (bar):	5 bar			
Maximum Hot Water Temperature °C:	60°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single			
Isolation Included:	No			

Features:

- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- Robust metal fixing nut to secure the tap in place reducing the risk of loosening over time.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years.
 Salt spray tested to ensure added durability.
- 10-year parts and 1 year labour guarantee for peace of mind.
- Also available in black and brushed brass.
- Co-ordinating Bathroom taps available.

Product Certifications:





WRAS Cert. Number: 2309900 WRAS Expiry Date: 30/09/2028

For more products, visit our website: http://www.bristan.com



Dimensions (measurements in mm)





Flow Rates (I/min)								
System Pressure (bar)	0.2	0.5	1	2	3	5		
SAF BF C (mixed)	13.9	22.4	32.1	44.6	54.6	70.5		

TECHNICAL DATA SHEET



