SAF BSM C

SAFFRON Tap Range Saffron Bath Shower

Saffron Bath Shower Mixer Chrome



Specification					
Product Type:	Bathroom Taps				
Main Construction Material:	Brass				
Mount Type:	Deck				
Handle Type:	Loop				
Connection Inlet:	3/4" BSP				
Connection Outlet:	M24 Recessed Honeycomb Aerator				
Number of Tap Holes:	2				
Valve/Cartridge Type:	3/4" Short Stem Ceramic Disc Valve				
Plumbing System Requirements:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.3 bar				
Maximum Dynamic Pressure (bar):	5 bar				
Maximum Hot Water Temperature °C:	60°C				
Maximum Static Pressure (bar):	10 bar				
Flow Type:	Single				
Isolation Included:	No				

Features:

- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- Robust metal fixing nut to secure the tap in place reducing the risk of loosening over time.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years. Salt spray tested to ensure added durability.
- Rub clean handset limescale and debris build-up is quickly and easily removed by rubbing a finger or a cloth over the nozzles.
- 10-year parts and 1 year labour guarantee for peace of mind.
- Also available in black and brushed brass
- Co-ordinating Bathroom taps and Recess shower available.

Product Certifications:





Kiwa Certification No: 2312720 Kiwa Expiry Date: 11/12/2028

WRAS Certification No: 2312356 WRAS Expiry Date: 31/12/2028





Dimensions (measurements in mm) 140 95 050 150 180 35 0110 240

Flow Rates (I/min)								
System Pressure (bar)	0.3	0.5	1	2	3	5		
Through Bath Filler (mixed)	9.6	15.8	23.4	33.4	40.7	52.5		
Through Handset (mixed)	3.9	5.1	7.5	11	14	18.6		

TECHNICAL DATA SHEET



